

# Solid Cushion Tires



## Key Specifications

Tire Size	Tread Pattern	Cushion Rows	S.W.	Tread Depth	Outer Diameter	Rim Size	Weight (lbs)	Load Capacity (lbs)
19x8-12	DT	1	7.1"	1.0"	19.1"	8"x12"	83 lbs	2,640 lbs
23X5.7-12	DT	1	5.7"	1.7"	22.4"	4"x12"	87 lbs	2,863 lbs
23x8.5-12	DT	1	7.3"	1.7"	22.8"	5"x12"	101 lbs	3,310 lbs
27x8.5-15	DT	1	7.9"	2.0"	26.6"	5.5"x15"	143 lbs	4,410 lbs
30x10-16	DT	4	9.1"	2.7"	30.2"	6"x16"	197 lbs	6,600 lbs
30x10-16	AT	4	9.4"	2.1"	30.2"	6"x16"	217 lbs	4,850 lbs
30x8.5-16	DT	2	7.4"	1.9"	30.2"	6"x16"	175 lbs	4,190 lbs
31x10.5-20	DT	2	9.1"	1.5"	31.8"	7"x20"	233 lbs	6,600 lbs
31x8-16	SS	4	7.1"	-	31.8"	6"x16"	217 lbs	5,370 lbs
32.5x15-16	DT	4	14.4"	2.3"	32.3"	11.25"x16"	347 lbs	11,020 lbs
33x12-16	DT	2	10.8"	3.4"	32.7"	8"x16"	271 lbs	8,250 lbs
33x12-20	DT	2	10.8"	2.8"	32.7"	7.5"x20"	270 lbs	7,700 lbs
33x12-16	AT	4	10.2"	2.6"	32.8"	8"x16"	300 lbs	8,270 lbs
36x14-20	DT	2	13.5"	2.0"	36.0"	11"x20"	438 lbs	10,580 lbs
36.5x14-20	DT	2	13.6"	3.5"	36.2"	11"x20"	437 lbs	10,580 lbs
36.5x12-20	DT	2	11.8"	3.1"	36.8"	8"x20"	703 lbs	7,937 lbs
38.5x14-20	DT	2	13.5"	2.4"	38.5"	11"x20"	489 lbs	9,260 lbs
18.0-20	DT	2	16.9"	4.1"	41.7"	12x20"	937 lbs	14,990 lbs
385/65-24	DT	2	14.2"	2.0"	41.7"	10"x24"	595 lbs	14,330 lbs
385/70-20	DT	2	14.2"	2.0"	41.7"	10"x24"	677 lbs	14,330 lbs
50x16-24	AT	2	15.8"	3.1"	49.2"	11.5"	1,076 lbs	17,637 lbs
50x13-24	AT	2	12.6"	3.4"	49.2"	8.5"x24"	847 lbs	15,180 lbs
15.5-25	DT	2	15.2"	3.7"	50.0"	11.25"x24"	1043 lbs	17,600 lbs
50x13-24	DT	2	12.6"	4.2"	50.0"	8.5"x24"	789 lbs	15,180 lbs
53X14-24	AT	2	13.4"	3.5"	52.0"	10"x24"	1,000 lbs	17,600 lbs
17.5-25	DT	2	17.3"	4.9"	52.8"	14"x25"	1197 lbs	18,700 lbs
17.5-25	AT	2	17.3"	5.8"	52.8"	14"x25"	1311 lbs	18,700 lbs
17.5-25	SS	2	17.3"	-	52.8"	14"x25"	1424 lbs	20,900 lbs
53X14-24	DT	2	13.8"	4.5"	52.8"	10"x24"	968 lbs	17,600 lbs
53X14-24	RT	2	14.2"	4.7"	53.1"	10"x24"	1,052 lbs	17,600 lbs
20.5-25	AT	2	20.5"	3.7"	58.3"	17"x25"	1970 lbs	21,200 lbs
20.5-25	SS	2	20.5"	-	58.3"	17"x25"	2143 lbs	23,150 lbs
16.00-25	AT	-	16.1"	3.8"	59.1"	11.25"	1400 lbs	28,660 lbs
23.5-25	AT	2	23.2"	7.5"	63.4"	19.5"x25"	2661 lbs	26,450 lbs
23.5-25	SS	2	23.2"	-	63.4"	19.5"x25"	2892 lbs	28,600 lbs
18.0-25	RT	-	19.3"	3.3"	63.6"	13x25"	1951 lbs	33,069 lbs
23.5-25	DT	2	22.8"	7.5"	63.8"	19.5"x25"	2491 lbs	26,450 lbs
26.5-25	AT	2	25.6"	8.4"	67.7"	22"x25"	3461 lbs	32,000 lbs
26.5-25	SS	2	25.6"	-	67.7"	22"x25"	3759 lbs	35,200 lbs
26.5-25	DT	2	26.4"	8.4"	68.9"	22"x25"	3479 lbs	32,000 lbs
29.5-25	AT	2	29.1"	7.9"	73.6"	25"x25"	4773 lbs	40,800 lbs
35/65-33	AT	2	33.5"	7.8"	79.9"	28"x33"	6010 lbs	52,900 lbs

Weight may vary based on custom rim specifications; The above specifications are provided for reference only and may change without notice.